


# Product data sheet

## Higo - Motor - L1019A

### Male cable connector

L1019AG P 00 AZ 1000

<https://www.higoconnector.com/en/e-bike-connector/l1019agp00az1000>



## Specifications

### General Characteristics

<b>Number of contacts</b>	10 (3+7)
<b>Connector shape</b>	Plug
<b>Gender</b>	Male
<b>Color</b>	Black
<b>Upper temperature</b>	80 °C
<b>Lower temperature</b>	-25 °C
<b>Locking</b>	Screw locking
<b>IP Protection</b>	IP67
<b>Mating cycles</b>	200 Mating times
<b>Connector diameter</b>	19 mm
<b>Fitting length</b>	114 mm
<b>Cable Length</b>	1000 mm
<b>Cable diameter</b>	8.5 mm
<b>Wire section</b>	3 x 4,0 + 7 x 0,14 mm <sup>2</sup>
<b>Remark</b>	Other cable length/type on request

# Product data sheet

## Higo - Motor - L1019A

### Male cable connector

### Electrical Parameters

<b>Rated current</b>	30 / 2 A
<b>Rated voltage</b>	48 V AC / 60 V DC
<b>Max. insulation resistance</b>	$\geq 20 \text{ M}\Omega$
<b>Max. contact resistance</b>	$\leq 10 \text{ M}\Omega$

### Material

<b>Material jacket</b>	PVC
<b>Insulation wire</b>	Teflon
<b>Material of contact</b>	Brass
<b>Contact plating</b>	Gold over Nickel