

# Product data sheet

## Higo - Motor - L1114A

### Male cable connector

L1114AG P 00 FF 1000

<https://www.higoconnector.com/en/e-bike-connector/l1114agp00ff1000>



## Specifications

### General Characteristics

<b>Number of contacts</b>	11 (3+8)
<b>Connector shape</b>	Plug
<b>Gender</b>	Male
<b>Color</b>	Black
<b>Upper temperature</b>	80 °C
<b>Lower temperature</b>	-25 °C
<b>Locking</b>	Screw locking
<b>Protection degree</b>	IP67
<b>Mating cycles (times)</b>	200 Mating times
<b>Connector diameter</b>	14 mm
<b>Fitting length</b>	80 mm
<b>Cable Length</b>	1000 mm
<b>Wire section</b>	3 x 2,0 + 8 x 1,4 mm <sup>2</sup>
<b>Remark</b>	Other cable length/type on request

# Product data sheet

## Higo - Motor - L1114A

### Male cable connector

### Electrical Parameters

<b>Rated current</b>	20 / 2 A
<b>Rated voltage</b>	48 V AC / 60 V DC
<b>Max. insulation resistance (M )</b>	≥20 MΩ
<b>Max. contact resistance (M )</b>	≤10 MΩ

### Material

<b>Material jacket</b>	PVC
<b>Insulation wire</b>	FEP
<b>Material of contact</b>	Copper Alloy
<b>Contact plating</b>	Silver over Nickel