

# Product data sheet

## Higo - Motor - L315A

### Female cable connector

L315AM P 01 B8 1000

<https://www.higoconnector.com/en/e-bike-connector/l315amp01b81000>



## Specifications

### General Characteristics

<b>Number of contacts</b>	3
<b>Gender</b>	Female
<b>Color</b>	Black
<b>Upper temperature</b>	80 °C
<b>Lower temperature</b>	-25 °C
<b>Locking</b>	Screw locking
<b>Protection degree</b>	IP67
<b>Mating cycles (times)</b>	200 Mating times
<b>Connector diameter</b>	15 mm
<b>Fitting length</b>	90 mm
<b>Cable Length</b>	1000 mm
<b>Cable diameter</b>	9 mm
<b>Wire section</b>	3 x 4,0 mm <sup>2</sup>
<b>Remark</b>	*Rated current: 35A, 2 power pin loaded 28A / 2A, 3 power pin loaded Other cable length/type on request

# Product data sheet

## Higo - Motor - L315A

### Female cable connector

### Electrical Parameters

<b>Rated current</b>	*35 A
<b>Rated voltage</b>	48 V AC / 60 V DC
<b>Max. insulation resistance (M )</b>	≥20 MΩ
<b>Max. contact resistance (M )</b>	≤10 MΩ

### Material

<b>Material jacket</b>	PVC
<b>Insulation wire</b>	Teflon
<b>Material of contact</b>	Phosphor Bronze
<b>Contact plating</b>	Gold over Nickel