

# Product data sheet


## Higo - Battery - S824A

### Male cable connector

## Self-locking, button release

S824AG A 00 FP 1000

<https://www.higoconnector.com/en/e-bike-connector/s824aga00fp1000>



## Specifications

### General Characteristics

<b>Number of contacts</b>	8 (2+6)
<b>Connector shape</b>	Angled plug
<b>Gender</b>	Male
<b>Color</b>	Black
<b>Upper temperature</b>	80 °C
<b>Lower temperature</b>	-25 °C
<b>Locking</b>	Self-locking, button release
<b>Protection degree</b>	IP67
<b>Mating cycles (times)</b>	3000 Mating times
<b>Connector diameter</b>	25 mm
<b>Cable Length</b>	1000 mm
<b>Cable diameter</b>	13.6 mm
<b>Wire section</b>	2 x 10,0 + 6 x 0,20 mm <sup>2</sup>

# Product data sheet



## Higo - Battery - S824A

### Male cable connector

**Remark**

Other cable length/type on request

# Product data sheet

## Higo - Battery - S824A

### Male cable connector

#### Electrical Parameters

<b>Rated current</b>	70 / 2 A
<b>Rated voltage</b>	48 V AC / 60 V DC
<b>Max. insulation resistance (M )</b>	≥20 MΩ
<b>Max. contact resistance (M )</b>	≤10 MΩ

#### Material

<b>Material jacket</b>	PVC
<b>Insulation wire</b>	PVC
<b>Material of contact</b>	Brass
<b>Contact plating</b>	Gold over Nickel