

Product data sheet

Higo - Battery - S828A

Male cable connector, self-locking

Charging & discharging in 1, self-locking

S828AG A 00 FM 1000

<https://www.higoconnector.com/en/e-bike-connector/s828aga00fm1000>



Specifications

General Characteristics

Number of contacts	8 (2+2+4)
Connector shape	Angled plug
Gender	Male
Color	Black
Upper temperature	80 °C
Lower temperature	-25 °C
Locking	Self-Locking
Protection degree	IP67
Mating cycles (times)	3000 Mating times
Connector diameter	28,05 mm
Cable Length	1000 mm
Cable diameter	8 mm
Wire section	2 x 2,5 + 2 x 1,3 + 4 x 0,2 mm ²

Product data sheet

Higo - Battery - S828A

Male cable connector, self-locking



Remark

Other cable length/type on request

Product data sheet

Higo - Battery - S828A

Male cable connector, self-locking

Electrical Parameters

Rated current	25 / 10 / 2 A
Rated voltage	48 V AC / 60 V DC
Max. insulation resistance (M)	≥20 MΩ
Max. contact resistance (M)	≤10 MΩ

Material

Material jacket	PVC
Insulation wire	FEP
Material of contact	Brass
Contact plating	Gold over Nickel