


# Product data sheet

## Higo - Signal - Mini F

### Mini F male cable connector

Z209FG P 00 AW 1000

<https://www.higoconnector.com/en/e-bike-connector/z209fgp00aw1000>



## Specifications

### General Characteristics

<b>Number of contacts</b>	2
<b>Connector shape</b>	Plug
<b>Gender</b>	Male
<b>Color</b>	Red
<b>Upper temperature</b>	80 °C
<b>Lower temperature</b>	-25 °C
<b>Locking</b>	Push-on (no locking)
<b>Protection degree</b>	IP66/IP67
<b>Mating cycles (times)</b>	200 Mating times
<b>Connector diameter</b>	see drawing mm
<b>Fitting length</b>	54 mm
<b>Cable Length</b>	1000 mm
<b>Cable diameter</b>	2.4 mm
<b>Wire section</b>	0.14 mm <sup>2</sup>

# Product data sheet

## Higo - Signal - Mini F

### Mini F male cable connector



### Electrical Parameters

Rated current	2 A
Rated voltage	48 V AC / 60 V DC
Max. insulation resistance (M )	$\geq 20 \text{ M}\Omega$
Max. contact resistance (M )	$\leq 10 \text{ M}\Omega$

### Material

Material jacket	TPU
Insulation wire	Teflon
Material of contact	/