

# Product data sheet



## Higo - Battery - Z624B

Battery male panel mount connector 48V code, no locking (push-on)

### Only for use in 48V applications

Z624BG C 03 D1 0300

<https://www.higoconnector.com/en/e-bike-connector/z624bgc03d10300>



## Specifications

### General Characteristics

<b>Number of contacts</b>	6 (2+4)
<b>Connector shape</b>	Panel mount
<b>Gender</b>	Male
<b>Color</b>	Black
<b>Upper temperature</b>	80 °C
<b>Lower temperature</b>	-25 °C
<b>Locking</b>	Push-on (no locking)
<b>Protection degree</b>	IP67
<b>Mating cycles (times)</b>	3000 Mating times
<b>Connector diameter</b>	28.5 mm
<b>Cable Length</b>	Single wires 300 mm
<b>Wire section</b>	2 x 2,0 + 4 x 0,34 mm <sup>2</sup>
<b>Remark</b>	Other cable length/type on request

# Product data sheet

## Higo - Battery - Z624B

Battery male panel mount connector 48V code, no locking (push-on)

### Electrical Parameters

<b>Rated current</b>	25 / 5 A
<b>Rated voltage</b>	48 V AC / 60 V DC
<b>Max. insulation resistance (M )</b>	≥20 MΩ
<b>Max. contact resistance (M )</b>	≤10 MΩ

### Material

<b>Material of contact</b>	Phosphor bronze
<b>Contact plating</b>	Gold over Nickel