


# Product data sheet

## Higo - Battery - Z718A

### Male plug connector

Z718AG P 00 GG 1000

<https://www.higoconnector.com/en/e-bike-connector/z718agp00gg1000>



## Specifications

### General Characteristics

<b>Number of contacts</b>	7 (2+5)
<b>Connector shape</b>	Plug
<b>Gender</b>	Male
<b>Color</b>	Black
<b>Upper temperature</b>	80 °C
<b>Lower temperature</b>	-25 °C
<b>Locking</b>	Push-on (no locking)
<b>Protection degree</b>	IP67
<b>Mating cycles (times)</b>	3000 Mating times
<b>Connector diameter</b>	10 mm
<b>Fitting length</b>	50 mm
<b>Cable Length</b>	1000 mm
<b>Cable diameter</b>	6.8 mm
<b>Wire section</b>	2 x 2,5 + 5 x 0,2 mm <sup>2</sup>
<b>Remark</b>	Other cable length/type on request

# Product data sheet

## Higo - Battery - Z718A

### Male plug connector

### Electrical Parameters

<b>Rated current</b>	25 / 2 A
<b>Rated voltage</b>	48 V AC / 60 V DC
<b>Max. insulation resistance (M )</b>	≥20 MΩ
<b>Max. contact resistance (M )</b>	≤10 MΩ

### Material

<b>Material jacket</b>	PVC
<b>Insulation wire</b>	Teflon
<b>Material of contact</b>	Brass
<b>Contact plating</b>	Gold